




CE

Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>9400 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Protection class	<b>IP65</b>



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI029046CW_PW
Power	100 W
Nominal current	435 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	9400 lm (120°)
Luminous flux**	9400 lm (360°)
Light efficiency	94 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP65
Colour	Black
Dimension (axbxc)	270x210x27 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux