

CE

---


Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>115 °</b>
Protection class	<b>IP54</b>		

---

 Declaration of Conformity

**Technical data:**

Product code	SLI031037NW_PW_CZUJNIK
Power	40 W
Nominal current	177 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	5300 lm (360°)
Luminous flux**	3200 lm (360°)
Light efficiency	133 lm/W
Luminous intensity	1160 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	115 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 +40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
Protection class	IP54
Colour	White
Dimension (axbxc)	485x70 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC
Other	MV Sensor ,



\*Applies to the LED source used. \*\*Luminaire luminous flux