



| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 30 W | Voltage | 230 V |
| Luminous flux* | 4300 lm (360°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 120 ° |
| Protection class | IP20 | | |



See more on dedicated page 



 User manual





 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|----------------------------------|
| Product code | SLI035055NW_PW |
| Power | 30 W |
| Nominal current | 132 mA |
| Voltage | 230 V |
| Energy consumption | 30 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 4300 lm (360°) |
| Luminous flux** | 3600 lm (360°) |
| Light efficiency | 143 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum/Steel/TWORZYWO SZTUCZNE |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 595x595x28 mm |
| For use | Inside |
| Assembly method | surface mounted, recessed |
| Application | INT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux