



---

|                  |                      |                    |               |
|------------------|----------------------|--------------------|---------------|
| Power            | <b>2,9 W</b>         | Voltage            | <b>12 V</b>   |
| Luminous flux*   | <b>170 lm (120°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour     | <b>Neutral white</b> | Beam angle         | <b>120 °</b>  |
| Protection class | <b>IP20</b>          |                    |               |

---



 Photometric file

**Technical data:**

|                              |                        |
|------------------------------|------------------------|
| Product code                 | SLI040038NW            |
| Power                        | 2,9 W                  |
| Nominal current              | 242 mA                 |
| Voltage                      | 12 V                   |
| Energy efficiency classe     | G                      |
| Energy consumption           | 4 kWh/1000h            |
| Frequency                    | DC Hz                  |
| Protection class             | III                    |
| Power factor                 | 1                      |
| Useful luminous flux*        | 170 lm (120°)          |
| Luminous flux**              | 170 lm (360°)          |
| Light efficiency             | 58 lm/W                |
| Colour temperature           | 4000 K                 |
| Light colour                 | Neutral white          |
| Beam angle                   | 120 °                  |
| RA                           | 80                     |
| Uniformity of color SDCM max | 5                      |
| Dimmable                     | Yes                    |
| Working temperature range    | -20/+40 °              |
| Lifespan                     | 17000 h                |
| Housing material             | PLASTIC                |
| Protection class             | IP20                   |
| Colour                       | SREBRNY                |
| Dimension (axbxc)            | 68x7 mm                |
| For use                      | Inside                 |
| Assembly method              | On the ceiling         |
| Application                  | INT                    |
| Made in                      | PRC                    |
| Other                        | Sensor range: 2 - 4m , |



\*Applies to the LED source used. \*\*Luminaire luminous flux