



CE

Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2200 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>110 °</b>
IK	<b>6</b>	Protection class	<b>IP44</b>



See more on dedicated page 





 User manual



 Photometric file

**Technical data:**

Product code	SLI043014CW_PW
Power	18 W
Nominal current	94 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.8
Useful luminous flux*	2200 lm (360°)
Luminous flux**	1500 lm (360°)
Light efficiency	122 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PA6+Aluminum
IK	6
Protection class	IP44
Colour	White
Dimension (axbxc)	190x30 mm
Mounting hole	155 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux